



# FOF ROOF WINDOW



FOF ROOF WINDOW	
<b>Applicable</b>	In public and domestic buildings In heated, inhabited rooms In roof pitch range of 15°- 90° Suitable on all roofings from 0 to 50 mm
<b>Features</b>	Centre pivot Slim frame Elegant bottom handle Two passive ventilation positions via handle Easy installation 10 year guarantee
<b>Material   Wood and finishing</b>	Kiln-dried laminated pine wood Timber from FSC certified forests Knot free visible surfaces Fungicide protection Acrylic lacquer

<b>Cover parts</b>	Aluminium, lacquered, RAL 7043
<b>Handle</b>	Ergonomically designed moulded zinc handle, lacquered
<b>Hinge</b>	Pivot hinge

VARIANT		500
<b>Pane</b>	Construction	4-17-3
	24 mm double glazing	■
	Low E	■
	Gas (argon)	■
	Ug (W/m²K)	1.1
	Total solar energy transmittance	0.62
	Uw (W/m²K)	1.6
	Water tightness	E1050
	Air permeability	Class 3
	Resistance to wind load	Class C4
	Sound reduction	30 (-1,-5) dB
<b>Colour</b>	Natural wood	■

MEASURES								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
FOF C2R	55 x 72 cm	55,0 cm	71,9 cm	39,8 cm	59,0 cm	37,3 cm	53,1 cm	0,198
FOF F6R	66 x 112 cm	66,0 cm	111,9 cm	50,8 cm	99,0 cm	48,3 cm	93,1 cm	0,449
FOF M4R	78 x 92 cm	78,0 cm	91,9 cm	62,8 cm	79,0 cm	60,3 cm	73,1 cm	0,440
FOF M6R	78 x 112 cm	78,0 cm	111,9 cm	62,8 cm	99,0 cm	60,3 cm	93,1 cm	0,561
FOF M8R	78 x 134 cm	78,0 cm	133,9 cm	62,8 cm	121,0 cm	60,3 cm	115,1 cm	0,694
FOF S6R	114 x 112 cm	114,0 cm	111,9 cm	98,8 cm	99,0 cm	96,3 cm	93,1 cm	0,896

COMPATIBILITY TABLE		
SIZE CODE	FLASHING 0-50 mm	AWNING BLIND
C2R	ZO C2R	MIR CXA
F6R	ZO F6R	MIR FXA
M4R	ZO M4R	MIR MXA
M6R	ZO M6R	MIR MXA
M8R	ZO M8R	MIR MXA
S6R	ZO S6R	MIR SXA

10 years guarantee



CE EN 14351-1: 2006