

FOY ROOF WINDOW



FOY ROOF WINDOW
Applicable
In public and residential buildings
In heated, inhabited rooms
In roof pitch range of 15°- 90°
Suitable on all common roofings with proper flashing
Features
Centre pivot
Slim frame
Toughened glass
Elegant bottom handle
Two passive ventilation positions via handle
Easy installation
10 year guarantee
Material Wood and finishing
Kiln-dried laminated pine wood
Timber from FSC certified sources
Fungicide protection
Water based lacquer

Cover parts
Aluminium, lacquered, RAL 7043
Handle
Ergonomically designed moulded zinc handle, lacquered
Hinge
Pivot hinge

VARIANT	B900
Pane	
Construction	4-16-4H
24 mm double glazing	■
Low E	■■
Gas (argon)	■
Toughened glass	■
U _g (W/m ² K)	1.0
Total solar energy transmittance	0,55
U _w (W/m ² K)	1,3
Water tightness	E1200
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1,-5) dB
Colour	
Natural wood	■

MEASURES								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m ²
FOY C2R B900	55 x 72 cm	55,0 cm	71,9 cm	39,8 cm	59,0 cm	37,3 cm	53,1 cm	0,198
FOY F6R B900	66 x 112 cm	66,0 cm	111,9 cm	50,8 cm	99,0 cm	48,3 cm	93,1 cm	0,449
FOY M4R B900	78 x 92 cm	78,0 cm	91,9 cm	62,8 cm	79,0 cm	60,3 cm	73,1 cm	0,440
FOY M6R B900	78 x 112 cm	78,0 cm	111,9 cm	62,8 cm	99,0 cm	60,3 cm	93,1 cm	0,561
FOY M8R B900	78 x 134 cm	78,0 cm	133,9 cm	62,8 cm	121,0 cm	60,3 cm	115,1 cm	0,694
FOY S6R B900	114 x 112 cm	114,0 cm	111,9 cm	98,8 cm	99,0 cm	96,3 cm	93,1 cm	0,896

COMPATIBILITY TABLE				
SIZE CODE	FLASHING 16-50 MM	FLASHING 16-120 MM 0-16 mm with modifications	AWNING BLIND	BLACKOUT BLIND
C2R	ZO C2R	WO C2R	MIR CXA	DUR C2R 4212
F6R	ZO F6R	WO F6R	MIR FXA	DUR F6R 4212
M4R	ZO M4R	WO M4R	MIR MXA	DUR M4R 4212
M6R	ZO M6R	WO M6R	MIR MXA	DUR M6R 4212
M8R	ZO M8R	WO M8R	MIR MXA	DUR M8R 4212
S6R	ZO S6R	WO S6R	MIR SXA	DUR S6R 4212

